



MAJESTIC



EXTREME

Genmac provides one-source responsibility for the generating system and accessories.

- All units and components are prototype tested, factory build and production tested. A specific control procedure during the several stages of production ensures long life and reliability.
- Rugged 4 cycle heavy-duty Industrial diesel engine, of primary brands with direct fuel injection system and swirl intake ports combine for a low fuel consumption and excellent transient response.
- Powerful alternators with insulation system of H class and impregnation made with tropicalized epoxy resins, are used as standard.
- Generator set accepts one-step 100% of full load.
- The variation of the Voltage is maintained between +1% by sophisticated Electronic Voltage Regulators.
- Fully programmable AMF controller is supplied with auto start control system and digital instrumentation. Automatic device for setting the periodic exercise is integrated into the AMF.
- Heavy-duty built-in anti-vibration insulators assures lower noise and longer components life.
- Protection guards on rotating parts
- Fork-lifting facilities are supplied together with 4 lifting brackets on the base frame
- The Silent version consist of a weather-proof bolted modular pre-painted enclosure (2000/14/CE compliant) with hinged lockable doors, radiator coolant hatch, base mounted radiator coolant and engine oil drain lines. These items affords superior flexibility and ease of maintenance.
- A stub-up area is provided to make easier the electrical connection to the load.
- A wide range of accessories is provided on request in order to satisfy the needs of the user and to let the generator work in almost every condition.

RATINGS

Model	Voltage	Phase	Hz	Power Factor	Standby KW	Standby KVA	Standby Amps	Prime KW	Prime KVA	Prime Amps	Starting KVA
G700P	400/230*	3	50	0,8	634	792	1145	576	720	1040	N/A
GU825P	480/277	3	60	0.8	660	825	993	600	750	903	N/A
GU825P	440/254	3	60	0.8	660	825	1084	600	750	985	N/A
GU825P	240/139	3	60	0.8	660	825	1987	600	750	1806	N/A
GU825P	220/127*	3	60	0.8	660	825	2168	600	750	1971	N/A
GU825P	208/120	3	60	0.8	652	815	2265	593	741	2059	N/A
GU825P	240/120	1	60	1.0	592	592	2468	539	539	2244	N/A

(*) Standard connection

RATING DEFINITION

Standby Rating: Applicable for supplying emergency power for the duration of normal power interruption limited to maximum 500h per year within the following maximum operating time: 100% load 25h per year, 90% load 200h per year.

No overload capability is permitted for this rating. "Limited Time running Power (LTP)" rating conforms to ISO 8528-1.

Prime Rating: Applicable for supplying power at a variable load for an unlimited number of hours per year. A 10% overload capability is available for one hour in twelve hours periods. This rating conforms to ISO 8528-1 "Prime Running Power (PRP)".

STANDARD REFERENCE CONDITIONS:

The above mentioned power data are calculated with: air temeparture of 25°C (77°F); 99kPa of barometric pressure, 100m of altitude a.s.l and 30% of relative humidity. For different conditions please refer to the derating factor's table specific for this engine.

INSTALLATION AND APPLICATION DATA

	Units	50 Hz		60 Hz		
		PRP	LTP	PRP	LTP	
General	Emission certificates	NOT CERTIFICATED				
	Noise level (silent version)	dB(a) 7mt 68		68		
	Rated Speed	Rpm 1500		1800		
Engine basic data	Engine Brand - Model	Perkins – 4006 23 TAG2A				
	Gross Engine Output	hp (KW) 895 (658)	980 (721)	930 (684)	1032 (759)	
	Number and arrangement of cylinders	6 vertical in-line				
	Type of air intake	Turbocharged and air-to-air charge cooled				
	Type of cooling	Water-cooled				
	Total displacement	liters (cu. In.)	22,9 (1397)			
	Bore x Stroke	mm (in.)	160 (6,3) x 190 (7,5)			
	Speed control	Electronic				
Speed drop	+- 0,5%					
Fuel system	Type of fuel	Diesel				
	Maximum Fuel Transfer Pump Lift-	m (ft)	N/A			
	Fuel consumption @ 25% load	Liters/h (gal/h)	N/A	N/A	N/A	N/A
	Fuel consumption @ 50% load	Liters/h (gal/h)	83 (21,9)	N/A	90 (23,8)	N/A
	Fuel consumption @ 75% load	Liters/h (gal/h)	121 (31,9)	N/A	129 (34,1)	N/A
	Fuel consumption @ 100% load	Liters/h (gal/h)	157 (41,5)	173 (45,7)	177 (46,7)	199 (52,5)
	Fuel tank capacity	Liters (gal)	400 (106)			
Autonomy @75% load	Hours	3		3		
Oil	Type of oil (for usage at std reference conditions)	SAE15W40				
	Total Quantity of oil (including filters)	Liters (qt.)	113 (119)			
	Maximum Oil consumption	N/A				
Coolant	Type of coolant	Glicole Mixture 50% Antifreeze – 50% demineralized water				
	Total quantity of coolant	Liters (qt)	105 (111)			
Air system	Air filter type	Dry Element				
	Max. perm. intake vacuum	kPa (in.H ₂ O)	N/A			
	Combustion air flow	m ³ /min (cf/min)	N/A	N/A	N/A	N/A
Exhaust system	Exhaust flow	m ³ /min (cf/min)	N/A	N/A	N/A	N/A
	Max. permissible exhaust backpressure	kPa (in.H ₂ O)	N/A			
	Outlet size diameter	mm (in.)	N/A			
Electrical system	Voltage of electric system	V	24			
	Starter motor capacity	A	N/A			
	Type of battery	Lead acid type				
Alternator	Number of poles	4				
	Number of bearings	1				
	Excitation	Self excited				
	Type of regulation	Automatic Voltage Regulation				
	Voltage accuracy	±1 % with any power factor and speed variations between -5% +30%				

STANDARD EQUIPMENTS

ENGINE

- Air Cleaner (Dry-cartridge type)
- Fuel Pump
- Fuel Filter
- Fuel stop solenoid
- Thermostat and Housing
- Dry Exhaust Manifold
- Blower Fan & Fan Drive
- Radiator - Unit Mounted
- Electric Starting Motor
- Housing & Flywheel
- Charging Alternator
- Battery Rack & Cables
- First filling of oil and filters
- First filling of coolant

GENERATOR

- Self-ventilated and drip-proof construction
- Synchronous, Brush-less, Self Exciting , Self Regulating
- Direct Coupled With Flex Disk
- 12 Leads winding
- Class H Insulation
- Drip-Proof Construction
- Humidity Tropical Protection
- Radio Interference Suppressor EMC Filter

EXHAUST

- Built-in Industrial Muffler (for Open generators)
- Built-in Residential Muffler (for Silent generators)
- Rain Cap

HANDLING

- Lifting and holding down points

BASE FRAME

- Heavy duty fabricated welded base plate with high quality steel.
- Heavy duty rubber anti-vibration mountings
- Stub-up area

PHYSICAL DATA

	Units	Majestic G700POA	Majestic GU825P	Extreme G700PSA	Extreme GU825P
Length	mm (in.)	4200 (165)	4200 (165)	5550 (219)	5550 (219)
Width	mm (in.)	1800 (71)	1800 (71)	1950 (77)	1950 (77)
Height	mm (in.)	2320 (91)	2320 (91)	2550 (100)	2550 (100)
Weight	Kg (lbs)	5410 (11927)	5460 (12037)	7840 (17284)	7890 (17394)

ELECTRICAL SYSTEM

- **Battery (for 50Hz is supplied as standard, for 60Hz is to be ordered separately)**
- Battery rack and cables
- Engine driven battery charger
- Battery disconnect switch

CANOPY (for silent units)

- Nylon hinges
- Heavy duty lockable handles in each door
- Large doors for easy access for service and monitoring
- Coolant refilling specific hatch
- Sound foam
- Modular bolted assembly after painting.
- Grey RAL 7035 "orange peel" specific powder coat paint for outdoor usage
- Weatherproof sealed joints.
- Cut using high precision laser technology.
- Bent using high precision numeric control technology.
- Glazed acoustic sealed control panel door.
- Fuel filler outside enclosure.
- In base oil and coolant drains

CONTROL PANEL (see specific section below)

- AMF controller C-08
- Fuel level gauge
- Three phase sensing for voltage and currents
- Battery charger (to be supplied by mains into the 208-240V range)
- Circuit breaker
- On/Off button
- Emergency stop button
- External ATS connection board
- EC Conformity in compliance with EN 60439-1

PACKAGING

- Nylon filming protection package
- Alternator, Engine and Generating set operator's manual are supplied together with electrical drawings

CONTROL PANEL



CIRCUIT BREAKER

The generators are supplied together with a circuit breaker that permits a thermal protection against overloads and magnetic protection against short-circuit.

COMMANDER C-08

C08 is a high performance, latest generation controller that includes a sophisticated digital multi-meter, an engine protection card and a controller with "Autostart" logic, "Automatic Mains Failure logic" and "Dual logic".

Its big display (320x240 pixel; visible area 115x85mm) permits to see all the main measures at the same time. With C08 controller a piece of equipment is no longer considered as a single entity, but controlled and operated keeping in mind the entire application system it belongs to and its environment.

Its easy-to-use keyboard has the possibility of blocking all or some of the keys to avoid tampering in the system. Here follows a list of the features of the controller:

Programmable I/O

- > 10-digital inputs
- > 20-analog inputs
- > 8-relays output 5A

Communication ports

- > 2-RS232 on the rear side
- > 1-USB on the front

Special Functions included

- > Remote start and stop
- > SCR
- > EJP - EJP/T
- > Start and stop in accordance to the mains KW (load sharing/shedding Logic)
- > Dummy load function
- > Programmable Rental hours (Stop on exceed)
- > Block of automatic and test modes
- > Generator starting for mains contactor fault
- > Output for function mode

Display Information

- > Battery voltage
- > Mains voltage three-phase L/L and L/N
- > Generator voltage three-phase L/L and L/N
- > Three-phase currents
- > Three-phase and global active, reactive and apparent powers.
- > Active, reactive and apparent energy meters.
- > Three-phase and global power factors
- > Power meter
- > Frequency
- > Oil pressure instrument
- > Engine temperature instrument
- > Fuel level instrument
- > Hours of autonomy in accordance to fuel consumption
- > Engine RPM value
- > Total starting attempts
- > Percent of good starting attempts
- > Working hours (re-settable)
- > Partial working hours (re-settable)
- > Warning and alarm about service/rental hours expiration
- > Internal working hour counter (non re-settable, to check effective engine working hours).

Alarms

- > High engine temperature alarm (digital sensor)
- > Low oil pressure alarm (digital sensor)
- > Temperature digital sensor fault
- > Fuel level warning (analog sensor)
- > Low fuel level alarm (analog sensor)
- > Fuel level analog sensor fault
- > Low fuel level alarm (digital sensor)
- > High battery voltage - Low battery voltage
- > Faulty battery - Battery charger alternator fault
- > "W" signal fault
- > Low engine speed - High engine speed
- > Starting failure - Mechanical failure
- > Emergency button
- > Stop failure
- > Low generator frequency - High generator frequency
- > Low generator voltage - High generator voltage
- > Asymmetric voltage generator
- > Generator short circuit
- > Generator overload
- > External generator protection
- > Generator wrong phases sequence
- > Mains wrong phases sequence
- > Wrong frequency setting
- > Generator contactor fault
- > Mains contactor fault
- > Several steps maintenance
- > Internal system error
- > Expired rental hours
- > n.8 programmable user alarms
- > Ambient temperature too high - Ambient temperature too low

Certificates and tests

- > IMQ certificate HALT test included (Highly Accelerated Life Test)

CANBUS readings and Parallel operation logic are available as an option.

OPTIONAL EQUIPMENTS

A wide range of optional equipments are available to satisfy all the needs of the installator. Please contact GenMac's sales department for full details of these and other options

ENGINE

- Starting aids (glow plugs-coolant heaters-oil heaters ..)
- Double-stage filters

GENERATOR

- Thermal protections
- Anti-condensation heaters
- Special treatment for usage in marine environmental conditions
- Full power alternator for single phase connection

EXHAUST

- Exhaust adapters
- Extension exhaust hose
- FAP filters

ELECTRICAL SYSTEM AND CONTROL PANEL

- Auxiliary sockets and plugs
- Oil pressure meter
- Water temperature meter
- Generator Monitoring/Remote control of complete system (with analog, GSM or Ethernet connection)
- Automatic Transfer Switches

HANDLING AND CANOPY

- Central lifting hook
- Slow drive trailers
- On-road Trailers
- Bigger Fuel tanks
- Double wall UL compliant fuel tanks
- Precision fuel sender

MAINTENANCE

- Consumable Filters and spares for each maintenance interval

WARNINGS

- Access to control panel and doors on both sides for inspection and maintenance is required.
- Adequate ventilation on both sides is required.

WARRANTY

Please refer to Genmac for warranty policy described into WG001 module.

All Specifications and Materials are subject to change without prior notice.



GENMAC Group:

Head Quarter

Genmac S.r.l.

42044 Gualtieri, (Reggio Emilia) Italy
via Don Minzoni, 13
Tel. (+39) 0522 828 179
Fax (+39) 0522 829 218

E-mail: info@genmac.it

Web space: www.genmac.it

Subsidiary

Genmac USA, Inc.

7060 NW 52nd STREET
MIAMI - FL 33166 - U.S.A.

Ph. (+1) 305 599 80 99

Fax (+1) 305 599 80 98

Toll Free Dial # 1-877-257-4541

E-mail : genmacusa@genmac-group.com

Web space: www.genmac-group.com

Distributed By: